









## Smart Multi-unit Charger

6bay / 12bay / 18bay

HPCMC6 / HPCMC12 / HPCMC18

# LCD/LED Display

LEDs display information for 7.4V batteries

LED DISPLAY	CHARGING STATUS
 Solid blue	Power supply connected
 Solid red	Battery charging
 Solid green	Fully charged
 Flashing red	Fault condition
 Flashing green	80% charged
 Solid orange	Charger reset

## Compact Design



6Bay

193x248x86mm



12Bay

390x248x86mm



18Bay

550x180x86mm



# Multiple Brands Supported



# Multiple Models Supported

**HYTERA:** HPCMC6/12/18H1, PD4, PD5, PD6, PD7, PD9 series

**MOTOROLA:** HPCMC6/12/18M1, DP2000/DP4000, HPCMC6/12/18M2, DEP450

**More models supported by request**

# Specifications

	MODEL	SPECIFICATIONS
Dimension (W*L*H)	6 Bay	193×248×86mm
	12 Bay	390×248×86mm
	18 Bay	550×180×86mm
Weight(Charger)	6 Bay	0.85 kg
	12 Bay	1.6 kg
	18 Bay	2.1 kg
Weight (Adaptor)	6 Bay	0.4 kg
	12 Bay	0.5 kg
	18 Bay	0.82 kg
Adaptor Input	6 Bay	100V - 240V AC / 50Hz - 60Hz 2.2A (max)
	12 Bay	
	18 Bay	
Adaptor Output	6 Bay	13.8V DC /5A
	12 Bay	13.8V DC /9A
	18 Bay	12V DC /9A
Charger Input	6 Bay	13-15V DC / 5A
	12 Bay	13-15V DC / 9A
	18 Bay	12V DC / 9A
Compatible Battery Type		Li-ion / LiPo / NiMH / NiCd
Recommended Operating Temperature		15°C - 30°C
Storage Temperature		0°C - 65°C
Charge Current		800mA
Certificate		FCC, CE,UL,RCM (Adaptor)